



EXTERIOR FINISH
AS SPECIFIED

QUAD-LOCK TIE

REINFORCED
CONCRETE CORE

QUAD-LOCK PANEL

INTERIOR GYPSUM
PLASTERBOARD FASTEN
TO TIES

LINTEL REINFORCEMENT
TO ENGINEER SPECIFICATION

WIND-LOCK TYPE FASTENER
OR SIMILAR

BLOCKING FOR RECESSED
WINDOW ATTACHMENT

INTERNAL WOOD BUCK
TO BE FASTENED TO CONCRETE
VIA SCREWS ON CONTACT SIDE

WINDOW FRAME BY OTHERS
FASTEN TO BLOCKING AS SHOWN

GLAZING



Quad-Lock (England) Ltd.
Unit B3, 1 Maws Centre
Jackfield, Shropshire
TF8 7LS

Tel : 01952 884931
Fax : 01952 883285
www.quadlock.co.uk

RECESSED WINDOW DETAIL

DATE:	2008-05-13	SCALE:	N.T.S.
REVISION NO:	R-00	PROJECT:	N/A
REVISION DATE:		CUSTOMER:	N/A
DRAWN BY:	Z. PROSTRAN	APPROVED BY:	H. M. KUSTERMANN
			DRAWING NO: 7.6.1

IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE REGULATIONS AND BUILDING CODE REQUIREMENTS CONCERNING THE USE OF THESE PRODUCTS.
IT IS FURTHER THE RESPONSIBILITY OF THE USER TO RESEARCH AND UNDERSTAND SAFE METHODS OF USE AND HANDLING OF THESE PRODUCTS.